



# 8CH 1080P NVR

## SCAS-N0810D

### General Features :

8CH FULL 1080P NVR, 1920\*1080, 1CH\*1080P Playback

HDMI, VGA, RJ-45, 2xUSB, White or Black Casing

1 SATA 2.5'/3.5' Hard Disk Interface, 1x4TB HDD Capacity

Remote Viewable by Smart Phone/Computer/Tablet With Internet Access



<b>Model</b>	<b>SCAS-N0810D</b>
<b>System</b>	
Main Processor	ARM Cortex A9 Processor
Operating System	Embedded LINUX
<b>Video</b>	
Input	8 Channel, Support 1920×1080, 1280×960, 1280×720 ect...
Output	1 VGA, 1 HDMI 1080P Out
<b>Alarm</b>	
Sensor Input	NO
Output	NO
Motion Detection	8 Channel
Email Alarm	Support
<b>Display</b>	
VGA	Resolution: 800×600, 1024×768, 1280×720, 1280×1024, 1920×1080
HDMI	Resolution: 720P(1280×720), 1080P(1920×1080)
Display Split	9 Channel / 8 Channel / 6 Channel / 4 Channel / 1Channel

Digital Zoom	YES
OSD	Camera Title, Time, Video Loss, Recording, Motion Detection
<b>Recording</b>	
Video Compression	H.264
Resolution	1080P(1920×1080) / 960P(1280×960) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	PAL : 1080P@200fps, 960P@200fps, 720P@200fps, D1@200fps NTSC: 1080P@240fps, 960P@240fps, 720P@240fps, D1@240fps
Record Mode	Manual\Timer\Motion Detection
<b>Playback &amp; Backup</b>	
Local Sync Playback	1CHx1080P
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Digital Zoom
Backup Mode	USB Device/Network
<b>Network</b>	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	HTTP, IPv4, TCP/IP, DNS, DHCP, NTP, DDNS

Onvif Version	Support Onvif 2.4
Web Browser	IE6-11, Firefox, Chrome (Under Windows System)
CMS Software	Support Windows XP / Windows Vista / Windows 7/ Windows 8
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
<b>Hard Disk Driver</b>	
Interface Type	1 SATA 2.5" Hard Disk
Capacity	Up to 4TB capacity
<b>General</b>	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC5V/2A
Working Environment	-10~55°C/10~90%
Dimension(WxDxH)	114mmx110mmx40mm
Weight	0.5KG (without HDD)