

ANALOG SPEED DOME

SCAPM6A22S70

General Features :

6" Medium Speed Dome Camera

Weatherproof Outdoor IP66

Φ 20x6PCS+ Φ 16x5PCS IR LEDS, IR Range: 100m

Lightning Protection: Transient Voltage 3000V



Model	SCAPM6A22S70
Camera	
Image Sensor	1/3" Super HAD II SONY CCD, Effio

Horizontal Resolution	Color 650TVL, Black 700TVL
S/N Ratio	>55db
PTZ	
Horizontal Rotation Speed	60°/s
Tilt Rotation Speed	45°/s
Horizontal Rotation Range	360°
Tilt Rotation Range	94°
Auto Flip	Horizontal 180°, Vertical 90°
A-B Scan	User programmable
A-B Scan Speed	1-9 speed setting available
360° Scan Speed	1-9 speed setting available
Dwell Preset	5-60s interval
Preset Points	220
Go to Preset Speed	200°/s
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
Pattern Scan	4 pcs
Pattern Scan Record	max.15 minutes, max.512 commands
Park Action	Home position, 360° scan/A-B scan/guard tour 1-3
Home Pos Time	1-60mins available
PWR on Action	Memory as power off/360° scan/A-B scan/Preset cruise1-3
Auxiliary Interface	

Communication Protocol	Pelco-D,Pelco-P
Communication	RS485
Baud Rate	1200/2400/4800/9600bps
General	
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Auto Control IR LED	PWM
OSD Menu	English
Power	DC12V/4A
IR Illumination Distance	100M
Power Consumption	≤ 15W
Lightning Protection	Transient voltage 6000V
Dimension	28x28x42(cm)
Weight	3.8kgs