

BULLET AHD/CVI/TVI

SCAVDK40

General Features :

Board Lens 6mm/F2.0

Φ 42X2PCS





Model NO.	SCAVDK40A100	SCAVDK40A130	SCAVDK40A200M	SCAVDK40A200H
Video Output Mode	AHD/CVBS	AHD/CVBS	AHD/CVBS	AHD/CVBS
Camera				
Image Sensor	OV9712S	IMX225	OV2710	IMX322
DSP	NVP2431H	NVP2431H	NVP2441H	NVP2441H
Image Resolution	720P/960H	960P/960H	1080P/960H	1080P/960H
Effective Pixels	1.0MP, 1280x720	1.3MP, 1280x960	2.1MP, 1920x1080	2.4MP, 1920x1080
TV System	PAL/NTSC			
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s			
Sync System	Internal			
Usable Illumination	0.01Lux	0.005Lux	0.001Lux	0.001Lux
S/N Ratio	≥50dB			
Scanning System	Progressive Scan			
Lens				
Focus Length	Board Lens 6mm/F2.0			
Focus Control	Fixed			
Lens Type	Fixed			
Pixels	2M Pixels			



Auto Iris Support	NO			
Night Vision				
Infrared LED	☉ 42X2PCS			
Infrared Distance	40M			
IR Status	Under 10 Lux by CDS			
IR Power On	CDS Auto Control			
Camera Features				
Day/Night	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W
OSD Menu Language	EN, CN, DE, FRA, IT, ES PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES PL, RU, PT, NL, TR
White Balance	Auto/Manual	Auto/Manual	Auto/Manual	Auto/Manual
Gain Control	Auto	Auto	Auto	Auto
Noise Reduction	3D NR	3D NR	3D NR	3D NR
Picture Adjustment	YES	YES	YES	YES
WDR	DWDR	DWDR	DWDR	DWDR
OSD Support	YES	YES	YES	YES
General				

Weatherproof Housing	YES, IP66
Anti-cut Bracket	NO
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	155(W) x 86(H) x102mm(D)
Weight	800g