

HD-IP SPEED DOME

SCIP-APM7A

General Features :

7" HD-IP Medium Speed Dome Camera

22x8PCS IR LEDES, IR Range: 120m, 18x or 22x Optical Zoom

Pan Speed: 60°/sec; Tilt Speed: 45°/sec

Lightning Protection: Transient Voltage 6000V



Model	SCAPM7A18H130	SCAPM7A22H200
Camera		
Image Sensor	1/3" Aptina Low Illumination 1.3MP CMOS	1/2.7" OmniVision Low Illumination 2MP CMOS
Horizontal Resolution	720P	1080P
S/N Ratio	>58db	
PTZ		
Horizontal Rotation Speed	60°/s	
Horizontal Rotation Range	360°	
Tilt Rotation Speed	45°/s	
Tilt Rotation Range	90°	
Auto Flip	Horizontal 180°, Vertical 93°	
Ratio Speed	Support	
360° Scan	User programmable	
360° Scan Speed	01-64speed setting available	
A-B Scan	User programmable	
A-B Scan Speed	01-64speed setting available	
PWR on Action	Memory/Tour/360 scan/AB scan/Home/Nop	
Park Time	1-60mins setting available	
Dwell Preset	1-60s interval available	
Preset Points	220	
Go to Preset Speed	200°/s	

Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
Auxiliary Interface	
Communication Protocol	Pelco-D, Pelco-P
Baud Rate	1200/2400/4800/9600bps
General	
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Auto Control IR LED	PWM
OSD Menu	English
Power	DC12V/4A
IR Illumination Distance	120M
Power Consumption	≤ 36W
Lightning Protection	Transient voltage 6000V
Dimension	32x32x43(cm)
Weight	7kgs