

HD-IP SPEED DOME

SCIP-APM7B

General Features :



Model	SCAPM7B18H130	SCAPM7B22H200
Camera		
Image Sensor	1/3" Aptina Low Illumination 1.3MP CMOS	1/2.7" OmniVision Low Illumination 2MP CMOS
Horizontal Resolution	720P	1080P
S/N Ratio	>58db	
PTZ		
Horizontal Rotation Speed	60°/s	
Horizontal Rotation Range	360°	
Tilt Rotation Speed	45°/s	
Tilt Rotation Range	90°	
Auto Flip	Horizontal 180°, Vertical 93°	
Ratio Speed	Support	
360° Scan	User programmable	
360° Scan Speed	01-64speed setting available	
A-B Scan	User programmable	
A-B Scan Speed	01-64speed setting available	

PWR on Action	Memory/Tour/360 scan/AB scan/Home/Nop
Park Time	1-60mins setting available
Dwell Preset	1-60s interval available
Preset Points	220
Go to Preset Speed	200°/s
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
Auxiliary Interface	
Communication Protocol	Pelco-D, Pelco-P
Baud Rate	1200/2400/4800/9600bps
General	
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Auto Control IR LED	PWM

OSD Menu	English
Power	DC12V/4A
IR Illumination Distance	120M
Power Consumption	≤ 36W
Lightning Protection	Transient voltage 6000V
Dimension	32x32x43(cm)
Weight	7kgs