

HD-TVI SPEED DOME

SCTVI-APM4E10

General Features :



Model	SCAPME410V200
Camera	
Image Sensor	1/3" SONY CMOS Sensor 2.4MP
Horizontal Resolution	1080P
S/N Ratio	>58db
PTZ	
Horizontal Rotation Speed	45°/s
Horizontal Rotation Range	360°
Tilt Rotation Speed	30°/s
Tilt Rotation Range	93°
Auto Flip	Horizontal 180°, Vertical 93°
Ratio Speed	Support
360° Scan	User programmable
360° Scan Speed	01-64speed setting available
A-B Scan	User programmable
A-B Scan Speed	01-64speed setting available
PWR on Action	Memory/Tour/360 scan/AB scan/Home/Nop
Park Time	1-60mins setting available
Dwell Preset	1-60s interval available
Preset Points	220
Go to Preset Speed	200°/s
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable

Auxiliary Interface	
Communication Protocol	Pelco-D, Pelco-P
Communication	RS485
Baud Rate	1200/2400/4800/9600bps
General	
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Auto Control IR LED	PWM
OSD Menu	English
Power	DC12V/3A
IR Illumination Distance	60M
Power Consumption	≤ 36W
Lightning Protection	Transient voltage 6000V
Dimension	29.5x28x17(cm)
Weight	3.4kgs