

# WIFI IP CAMERA

## SCWIPAS30

### General Features :



<b>Model NO.</b>	<b>SCWIPAS30</b>
<b>Camera</b>	
Image Sensor	1/4" Low Illumination 0.3MP CMOS Sensor
Processor	32Bit RSIC Embedded Processor
Resolution	640Hx480V
Output Pixel	VGA@30fps/QVGA@30fps/720P@1fps JPEG Capture
Effective Pixel	0.3.0M
Usable Illumination	0.8Lux/F1.4 (Colourful Model), 0.3Lux/F1. (B&W Mode)
PNP	YES
S/N Ratio	≥39dB
<b>Lens</b>	
Focus Distance	3.6mm
Focus Control	Fixed
Lens Type	Fixed
View of Angle	F1.4/56.14° ±5%
<b>Night Vision</b>	

Infrared LED	Φ 5X10PCS
Infrared Distance	10M
IR Status	Under 10 Lux By CDS
IR Control	IR turned on: Night vision view enabled, infrared Ray, ICR auto detect. IR turned off: Night vision disabled, infrared ray off, ICR stay in day view mode.
<b>Network</b>	
Input	1 Channel Internal -48dB Microphone
Output	1 Channel Line out(3.5mm phone jack)&Internal speaker(8Ω1W)
Sampling Frequency /Width	8KHz/16bit
Compression Format	ADPCM/32kbps
<b>Alarm</b>	
Motion Detection	Support
Action	Image E-mail/FTP video upload/GPIO
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP、 HTTP、 ICMP、 DHCP、 FTP、 SMTP

ONVIF	NO
P2P	YES, Support QR Code
POE	N/A
WIFI	WiFi802.11b/g/n
Security	WPS Encryption
Video Delay	0.3S (Within the Lan)
Bit Rate	32~4096kbps
Main Stream	VGA (640*480)@30fps
Sub Stream	QVGA (320*240)@30fps
JPEG Capture	NO
IE Brower	IE8-11, Google Chrome, Firefox
Smart Phone	iOS, Andriod OS
<b>Camera Features</b>	
Day/Night	Color/ B&W (IR-CUT )
Compression	Motion-JPEG,Support record AVI format
Image Config	Brightness/Contrast

Privacy Masking	NO
WDR	NO
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, English
<b>General</b>	
System Requirement	XP,Vista,iPhone iOS4.3,The android version 2.3 or higher
Hard Reset	NO
Storage	Support (up to 32G Micro SD card, loop recording)
CMS	1,4,9,16,25,36, 64,81-channel, no user number limitation , remote record, remote playback, alarm email ect.
Online Visitor	Support 4 online visitors simultaneously
P/T	Support (Pan:355°,Tilt:120°)
Preset Position	15
Power Supply	DC5±0.3V 2A
Power consumption	3.5W(IR opening )/7W(P/T working )
Application environment	Indoor

Operation Temperature	-10°C ~ +50°C RH90% Max
Storage Temperature	-20°C ~ +60°C RH90% Max
Dimension	200x120x179mm (LxWxH)
Weight	0.35kg
Installation	Wall mounting, ceiling mounting

